

Powr-Flite®

PERFECT SHINE EVERY TIME

Bring the life back to almost any hard-floor surface!



Item#
NM2000


Millenium Burnishers

Item# NM1600 - NM2000 - NM2000DC

The top-rated burnishers in the industry for value, performance, and durability.

- One-piece, all-metal handle housing, tube and trigger assembly for aggressive cleaning
- Floating handle for easy operation with safety start-up/lockout
- Full pad-to-floor contact, no compensating caster
- Flexible pad driver
- Patented one-piece housing

Conventional Burnishers



Powr-Flite Burnishers



HIGH SPEED BURNISHERS

Our burnishers give you years of trouble-free operation, making it easy to bring the life back to almost any hard floor surface! These machines offer exceptionally smooth operation with a flexible, self-adjusting pad driver that burnishes uneven surface areas evenly. Our patented design combined with precision-balanced weight distribution eliminates the need for a compensating caster. The entire pad is touching the floor, not just a couple of inches like conventional burnishers!



Item# NM2000DC

SPECIFICATIONS		NM1600 (1,600 RPM)	NM2000 (2,000 RPM)	NM2000DC (2,000 RPM)
PAD DIAMETER	20 Inches Full Pad-to-Floor Contact	✓	✓	✓
MOTOR	1-1/2 hp D.C. Rectified, UL Listed	✓	✓	✓
TRANSMISSION	Direct Drive			
	No Slip Deep "V" Belt Drive	✓	✓	✓
POWER CORD	75 ft. UL Listed 14/3 SJTW-A	✓		
	75 ft. UL Listed 12/3 SJTW-A		✓	✓
BASE HOUSING	One Piece, High Density Polyethylene	✓	✓	✓
PAD DRIVER	Factory Installed Rigid Block Drive			
	Flexible, Total 20" Floor-to-Pad Contact	✓	✓	✓
PAD PRESSURE (LBS)		15	16	16
HANDLE GRIPS	Anti-Fatigue, Soft to the Touch	✓	✓	✓
CORD STRAIN RELIEF	Heavy Duty Metal, Lock Nut and Spring	✓	✓	✓
HANDLE TUBE	All Chrome 1-1/2 Inch (Fixed)			
	All Chrome 1-1/2 Inch (Floating)	✓	✓	✓
HANDLE LEVER	Case Hardened Steel, Positive Lock	✓	✓	✓
OPERATING WHEELS	5 Inch Non-Marking-Self Lubricating	✓	✓	✓
	4 Inch Non-Marking-Self Lubricating			
TRANSPORT WHEELS	4 Inch Non-Marking-Self Lubricating	✓	✓	✓
WIRING	All Completely Enclosed in Housing	✓	✓	✓
SWITCH HOUSING	Non Conductive- Commercial Grade	✓	✓	✓
OPERATION CONTROL	Dual Lever On-Off Safety Switch Stress Absorbing. Left or Right Hand.	✓	✓	✓
WARRANTY	10 Yrs Housing, 2 Yrs. Motor, 1 Yr. On Parts & Workmanship	✓	✓	✓
WORK RATING (FT²/HR)		23,500	26,000	26,000
SHIPPING WEIGHT		89 lbs.	89 lbs.	89 lbs.



Easy access to motor and internal components! The completely enclosed motor and no exposed wires means longer lasting durability, with easy access for quick maintenance.



Strong reinforced handle yoke! Reinforcing the handle yoke and solid axle support provides strength and support for smoother operation and improved performance.